



# NetVanta 5305

## Multi-Slot Access Router Supporting up to Two T3's Worth of Bandwidth

### Product Features

- Six-slot, dual-Ethernet IP Access Router for Frame or PPP networks
- Dual auto-sensing 10/100Base-T interface for LAN segmentation
- Stateful inspection fire-wall for network security
- Command Line Interface (CLI) mimics *de facto* industry standard
- QoS for delay sensitive traffic like VoIP
- VLAN Trunking (802.1Q) for routing between VLANs
- Network Address Translation (NAT) conceals private IP addresses
- Optional VPN for secure corporate connectivity across the Internet
- Built-in DSU/CSU for circuit protection
- Feature-rich ADTRAN Operating System (AOS)
- Industry-leading five-year North American warranty

The NetVanta® 5305 is an access router designed for cost-effective Internet access, corporate Frame Relay, point-to-point connectivity, and Virtual Private Networking (VPN) for large-bandwidth applications supporting T3 networks.

#### Modular Hardware

Residing in a 3U high, 19" rackmountable metal enclosure, the NetVanta 5305 is a single platform that offers six interface slots and dual 10/100Base-T Ethernet LAN ports for true LAN segmentation or DMZ applications. A single slot within the NetVanta 5305 will house an Unchannelized T3, Octal T1/E1, or HSSI Wide Module.

#### Standard-based Protocols

The versatile hardware platform of the NetVanta 5305 is further complemented with the ADTRAN® Operating System (AOS). AOS allows for the support of static and default routes, demand and policy-based routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, RIP, and PIM Sparse Mode for multicast routing. In addition, AOS terminates Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, PPPoE, PPPoA, RFC 1483, and HDLC WAN protocols. Multihoming is also available to provide redundant or backup WAN links to multiple ISPs, guaranteeing a wide-area connection.

#### Security

For added security, AOS provides a powerful, high performance stateful inspection firewall. It will examine all incoming and outgoing packets against the security policies established by the IT manager. In addition, the firewall can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems. In addition, with the AOS Enhanced Feature Pack Upgrade, the NetVanta 5305 adds the support for IPsec compliant VPN. The NetVanta 5305 supports up to 2,000 simultaneous VPN tunnels, while supporting encryption algorithms like DES,

3DES, and AES. With this upgrade, the NetVanta 4305 is fully compatible with ADTRAN's IPsec VPN equipped NetVanta products: Ethernet switches, access routers, and VPN/Firewall appliances.

#### Quality of Service (QoS)

QoS is also supported for delay sensitive traffic like VoIP or video. To prioritize mission critical traffic and control network congestion, the NetVanta 5305 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish priority of IP packets routed over the WAN.

#### VoIP Ready

In combination with the QoS features, a specialized SIP Application Layer Gateway (ALG) allows SIP traffic to traverse NAT-enabled firewalls. For an enterprise network, this interoperability allows IP PBXs, phones, and other SIP-based devices to set up, tear down, and pass voice and call control messages seamlessly through the integral NAT-enabled firewall.

#### Administration

AOS offers a standard Command Line Interface (CLI) that mimics the widely adopted, industry *de facto* standard. Using an already familiar CLI virtually eliminates training costs associated with learning a new operating system or costly industry certifications. The CLI also allows for configuration scripts to be used, saved, and downloaded for a quick and easy recovery mechanism.

ADTRAN, the leader in WAN connectivity, offers reliable equipment that increases network performance, lowers cost, and positions networks for the future. The NetVanta 5305 is no exception. With this kind of corporate backing and product versatility, the NetVanta 5305 offers a low-cost, feature-rich access routing platform with the freedom for future expansion and network growth. In addition, these products are backed by an industry-leading five-year North American warranty, free firmware downloads, and world-class 24-hour technical support from ADTRAN.





# NetVanta 5305



## Multi-Slot Access Router Supporting up to Two DS3s Worth of Bandwidth

**ADTRAN, Inc.**  
Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000 voice  
256 963-8699 fax  
256 963-8200 fax back

**General Information**  
800 9ADTRAN  
info@adtran.com  
www.adtran.com

**Pre-Sales Technical Support**  
800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

**Where to Buy**  
877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

**Post-Sales Technical Support**  
888 423-8726  
support@adtran.com  
www.adtran.com/support

**ACES Installation & Maintenance Service**  
888 874-ACES  
aces@adtran.com  
www.adtran.com/support

**International Inquiries**  
256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

**For the regional office nearest you, visit:**  
www.adtran.com/regional

For more information regarding ADTRAN's export license, please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense)



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

64200990L1-8F 11.1 December 2005  
Copyright © 2005 ADTRAN, Inc.  
All rights reserved.

### Physical Interface

- **Six Wide Slots:** Unchannelized T3, Octal T1/E1 and HSSI
- **Dual LAN Ports:** Auto-sensing 10/100Base-T Ethernet Ports (RJ-45)
- Console Port

### Diagnostics LEDs

- **Power:** 1 and 2
- **Slots:** Status, Activity, Test
- **LANs:** link, transmit, receive

### Processor and Memory

- 1 GHz, Motorola 7447
- **RAM:** 256 MB
- **FLASH:** 32 MB

### Security

#### Firewall

- Stateful Inspection Firewall
- Denial of Service (DoS) Protection
- Access Control Lists
- Application Level Gateways (ALGs)

#### Network Address Translation

- Basic NAT (1:1), NAT (Many:1), and 1:1 Port Translation
- NAT compatible SIP ALG

#### Secure Management

- Multi-level access control
- RADIUS AAA
- TACACS+
- SSH CLI and SSL GUI
- Port Authentication (802.1x)

#### Optional Virtual Private Network (VPN)

- **IPSec Mode:** Tunnel
- **Encryption:** DES, 3DES, and AES
- **Diffie Hellman Group Support:**
  - Group 1: MODP 768
  - Group 2: MODP 1024
- **Hash Algorithms:** MD5-HMAC and SHA1-HMAC
- **Authentication Mechanisms:**
  - XAUTH
  - Secure ID
  - X.509 Digital certificates
  - DSS Signatures
  - Preshared keys
- **Key Management:** IKE (ISAKMP/Oakley)
- **IKE Modes:**
  - Main
  - Aggressive
  - Perfect Forward Secrecy
  - Mode Config
- Dead Peer Detection
- NAT Traversal V2

### Quality of Service (QoS)

- Class-based Weighted Fair Queuing, Low Latency, and Weighted Fair Queuing
- DiffServ marking and packet recognition
- Frame Relay Fragmentation

### Routing

- eBGP/iBGP
- OSPF
- RIP (v1 and v2)
- PIM Sparse Mode
- Demand Routing
- Policy-based Routing
- GRE
- Frame Relay
- Multilink Frame Relay
- PPP
- Multilink PPP
- PPPoE
- PPPoA
- IGMP v2
- RFC 1483
- HDLC
- PAP and CHAP
- Multihoming

### Frame Relay

- Point-to-point
- RFC 1490 Encapsulation (Multiprotocol Over Frame Relay)
- **LMI types:** LMI, ANSI (Annex D), CCITT (Annex A) and Static

### DHCP

- Client, Server, and Relay

### Administration

- Familiar Command Line Interface (CLI)
- n-Command™ support
- SNMP v2
- SYSLOG logging
- Email alerts (SMTP)
- Policy statistics

### Environment

- **Operating Temperature:** 0° to 50 °C (32° to 122 °F)
- **Storage Temperature:** -20° to 70 °C (-4° to 158 °F)
- **Relative Humidity:** Up to 95%, non-condensing

### Physical

- **Chassis:** 3U, rackmountable metal enclosure
- **Dimensions:** 5.25" H, 17.5" W, 10.25" D
- **Weight:** 21 lbs.
- **Power:** 85-250 VAC, 50/60 Hz, 325 W max.

### Agency Approvals

- FCC Part 68
- Industry Canada CS03
- UL & Canadian UL (CUL), IEC/EN, CSA
- CE Mark

### Product Includes

- User Manual, Quick Start Guide, AC Power Cord

## Ordering Information

Equipment	Part #
NetVanta 5305 Chassis	4200990L1
T3 Wide Module	1200832L1
Octal T1/E1 Wide Module	1202843L1
HSSI Wide Module	1200934L1
NetVanta 5305 Redundant AC Power Supply	1200840L1
VPN Upgrade	4200368L3
<b>Systems</b>	
NetVanta 5305 Chassis with T3 Wide Module	4200992L1

Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. n-Command is a trademark of ADTRAN Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.